

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)

**ISOPROPYL RUBBING
ALCOHOL 70%**

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

| | |
|---|---|
| Manufacturer's Name HYDROX LABORATORIES | Emergency Telephone Number 800-255-3924 |
| Address (Number, Street, City, State, and ZIP Code) 825 TOLLGATE ROAD | Telephone Number for Information 847-468-9400 |
| ELGIN, IL 60123 | Date Revised 5/18/11 |
| | Signature of Preparer (optional) |

Section II - Hazard Ingredients/Identity Information

| Hazardous Components (Specific Chemical Identity; Common Name(s)) | OSHA PEL | ACGIH TLV | Other Limits Recommended | % (optional) |
|---|--|-----------|--------------------------|--------------|
| ISOPROPYL RUBBING ALCOHOL (CAS #67-63-0) | PEL/TWA | | | |
| | 8 Hr. 400 ppm (OSHA/ACGIH) | | | |
| | STEL 500 ppm (OSHA/ACGIH) | | | |
| | REL TWA 10 Hr. 400 ppm (NIOSH) | | | |
| | 15 min. ceiling 800 ppm (NIOSH) | | | |
| ACUTE HEALTH HAZARD: 2 | | | | |
| FIRE HAZARD: 3 | | | | |
| REACTIVITY: 0 | | | | |

Section III - Physical/Chemical Characteristics

| | | | |
|------------------------------------|--|---|------|
| Boiling Point Approx. | 87° C | Specific Gravity (H ₂ O = 1) | 0.88 |
| Vapor Pressure (mm Hg.) Approx. | 33mmHg | Melting Point Percent Volatile | 100 |
| Vapor Density (AIR = 1) Approx. | 2.07 | Evaporation Rate (Butyl Acetate = 1) Approx. | 2.3 |
| Solubility in Water | COMPLETE. | | |
| Appearance and Odor | COLORLESS LIQUID, CHARACTERISTIC ODOR. | | |

Section IV - Fire and Explosion Hazard Data

| | | | |
|--|---|----------|-----------|
| Flash Point (Method Used) Approx. 77° F - TCC | Flammable Limits | LEL 2 | UEL 12 |
| Extinguishing Media | CARBON DIOXIDE, DRY CHEMICAL OR FOAM WATER FOG. | | |
| Special Fire Fighting Procedures | DILUTION OF BURNING LIQUID WITH WATER WILL AFFECT EXTINGUISHMENT. | | |
| Unusual Fire and Explosion Hazards | NONE. | | |

Section V - Reactivity Data

| | | | |
|---|---|---|---|
| Stability | Unstable | | Conditions to Avoid AVOID HEAT, SPARKS AND OPEN FLAME. |
| | Stable | X | |
| Incompatibility (<i>Materials to Avoid</i>) | ANHYDRIDE, ISOCYANATE, MONOMER AND ORGANO-METALLIC. | | |
| Hazardous Decomposition or Byproducts | BURNING MAY PRODUCE CARBON MONOXIDE AND CARBON DIOXIDE CONTAMINATION. | | |
| Hazardous Polymerization | May Occur | | Conditions to Avoid |
| | Will Not Occur | X | |

Section VI - Health Hazard Data

| | | | | |
|--|---------------------------|----------------------------|--------------------------|---------------------|
| Route(s) of Entry: | Inhalation? YES | Skin? NEGLIGIBLE | Ingestion? YES | Eyes? YES |
| Health Hazards (<i>Acute and Chronic</i>) GENERALLY USED AS A RUBDOWN. VAPOR IRRITATES EYES. HIGH CONCENTRATION OF VAPOR CAN IRRITATE RESPIRATORY TRACT, IS ANESTHETIC AND MAY CAUSE CNS DEPRESSION. | | | | |
| Carcinogenicity: NOT A CARCINOGEN | NTP? | IARC Monographs? | OSHA Regulated? | |
| Signs and Symptoms of Exposure GIDDINESS, HEADACHE, DIZZINESS AND NAUSEA. | | | | |
| Medical Conditions Generally Aggravated by Exposure PRE-EXISTING AND RESPIRATORY DISORDERS, MAY BE AGGRAVATED BY EXPOSURE. | | | | |
| Emergency and First Aid Procedures MOVE TO FRESH AIR. IF SWALLOWED, DO NOT INDUCE VOMITING AND CALL PHYSICIAN. FLUSH SKIN AND EYE CONTACT WITH WATER. | | | | |

Section VII - Precautions for Safe Handling and Use

| |
|--|
| Steps to Be Taken in Case Material is Released or Spilled. ELIMINATE ALL SOURCES OF IGNITION. SMALL SPILLS SHOULD BE FLUSHED WITH LARGE QUANTITIES OF WATER, LARGER SPILLS SHOULD BE COLLECTED FOR DISPOSAL. |
| Waste Disposal Method ATOMIZE INTO AN INCINERATOR WHERE PERMITTED UNDER APPROPRIATE FEDERAL, STATE, AND LOCAL REGULATIONS. |
| Precautions to Be taken in Handling and Storing DO NOT TAKE INTERNALLY. FLAMMABLE LIQUID. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. KEEP CONTAINER CLOSED. |
| Other Precautions |

Section VIII - Control Measures

| | | |
|--|--|---------|
| Respiratory Protection (<i>Specify Type</i>) AIR SUPPLIED MASKS IN CONFINED AREAS. | | |
| Ventilation | Local Exhaust PREFERRED | Special |
| | Mechanical (<i>General</i>) ACCEPTABLE | Other |
| Protective Gloves RUBBER OR VINYL GLOVES | Eye Protection GOGGLES | |
| Other Protective Clothing or Equipment EYE BATH AND SAFETY SHOWERS. | | |
| Work/Hygienic Practices HANDLE CAREFULLY; AVOID SPILLING. | | |

Section IX - Transportation Information

| | | |
|---|-----------------------------|---|
| Ground: Refer to CFR 49 (USA), and TDG regulations (Canada) | | |
| Shipping Name: Isopropanol | Hazard Class: 3 | Labels: One Gallon: : "Flammable Liquid (3) Isopropanol UN1219" |
| Identification Number: UN1219 | Packing Group: II | One Pint: "ORM-D Consumer Commodity" |

Disclaimer:

The contents of this MSDS are believed to be correct but do not purport to be all-inclusive and should only be used as a guide. Hydrox Laboratories, Inc. disclaims any express or implied warranty as to the accuracy of the above information and shall not be held liable for any direct, incidental or consequential damages resulting from the reliance on the above information.